

Cockpit Spray

Cleaner and Protector for Plastics
in a Spray Can

Basis: Silicon Oil

Issue: 2003-09-17

Technische Information
Technical Information

Henkel

Teroson

Product Description

Cockpit Spray is a silicon oil-based cleaning and restoring agent for plastic components in motor vehicles. The product contains deodorising and anti-static components and gives plastic parts a fresh silky sheen.

Application Areas

Cockpit Spray is suitable for the rejuvenation of plastic components in the interiors of cars. The product can also be used to treat leather, simulated leather and polished wood.

Technical Data

Colour:	colourless, transparent
Odour:	scented
Consistency:	thin liquid
Density:	approx. 0.76 g/cm ³ (full contents)
Solids:	approx. 6 %

Preliminary remark

Prior to application it is necessary to read the Safety Data Sheet for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed.

Application

The product is sprayed onto the desired area by pressing the spray button (hold can upright during use). The sprayed surface should be rubbed with a clean, dry cloth immediately after spraying.

Cockpit Spray should not be sprayed on windows, steering wheels or seats. A good method of using the product in areas close to such critical items is to spray the product onto a cloth and then wipe the surfaces concerned.

Caution

Although most automotive paints and interior plastics have excellent solvent resistance, it is recommended to perform a compatibility test prior to application, in order to avoid damage to the paint or the plastic surface.

Storage

Frost-sensitive	no
Recommended storage temp.	10°C to 20°C (never exceed 50°C)
Shelf-life	12 months

Packaging

Spray can

300 ml

Art.-No.108.11 B (D/GB/F/NL)

IDH-No. 142237

**Hazard Indications/
Safety Recommendations/
Transport Regulations**

see Safety Data Sheet

Important

The above data, particularly the recommendations for application and use of our products are based on our knowledge and experience. Due to different materials and conditions of application which are beyond our knowledge and control we recommend strongly to carry out sufficient tests in order to ensure that our products are suitable for the intended processes and applications. Except for wilful acts any liability based on such recommendations or any oral advice is hereby expressly excluded.

This Technical Data Sheet supersedes all previous editions.

Germany:

**Henkel KGaA
D-40191 Düsseldorf
Telefon (06221) 704-0
Telefax (06221) 704-698**

UK:

**Henkel Loctite Adhesives Ltd.
Watchmead
Welwyn Garden City
Hertfordshire AL 7 1 JB
Telephone (01707) 35 88 00
Telefax (01707) 35 89 00**