

TEROSON VR 710

Grease Spray April 2013

PRODUCT DESCRIPTION

TEROSON VR 710 provides the following characteristics:

Technology	Acid- and Silicone-Free Lubricant
Base	Synthetic Oil

TEROSON VR 710 is an acid-resistant and silicone-free, high-viscosity, synthetic oil-based liquid lubricant. It is water-repellent, protects against corrosion and moisture, does not become brittle at low temperatures, is highly stable and provides a durable, non-resinifying film of lubricant which is temperature resistant from - 40°C up to approximately 160°C.

APPLICATION AREAS

TEROSON VR 710 is suitable for mechanical drives such as chains, gearwheels, linkages and rollers. It can also be used for lubricating hinges, springs and steel cables.

TECHNICAL DATA

(Typical Test Results)

Colour	medium to light yellow
Odour	oily
Consistency	thick liquid
Density	approx. 0.85 g/cm ³
Cleaner	petrol

PRELIMINARY STATEMENT

Prior to application it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed.

Application

Shake the can vigorously before use until you can hear the ball rattle. TEROSON VR 710 is sprayed onto the part concerned by pressing the spray button (hold the can upright when spraying). Accurate application can be ensured by fitting the special tube.

Caution

This product does not contain combustible solvents with a flash-point below 100°C, but the TEROSON VR 710 can does contain a combustible propellant gas. Therefore the material must not be sprayed into the casings of operating machines, for example. It must only be used if there are no sources of ignition present, e.g. electrical contacts.

STORAGE

Frost sensitive	no
temperature stability	-40 to 160 °C
Recommended storage temperature	10 to 25 °C
Shelf life	12 months

Disclaimer

Note:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

TEROSON**TEROSON VR 710**

Grease Spray April 2013

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Henkel AG & Co. KGaA

D-40191 Düsseldorf, Germany
Phone: +49-211-797-0
www.henkel.com

Henkel Central Eastern Europe GmbH

A-1030 Wien, Austria
Phone: +43-1711-040
www.henkel.com

Henkel & Cie AG

CH-4133 Pratteln, Switzerland
Phone: +41-61-825-7000
www.henkel.com

